



## Altro Operetta™

Flooring type 地板类型		EN 10582	Resilient Floor 弹性地板
Thickness 厚度		EN ISO 24346	2mm
Wear layer 耐磨层		EN ISO 24340	0.7mm
Roll dimensions 成卷尺寸		EN ISO 24341	2.0m x 20.00m - 40m <sup>2</sup>
Weight 重量		EN ISO 23997	2.66kg/m <sup>2</sup>
Classification for use 使用等级分类		EN ISO 10874	34 & 43
Fire performance 防火		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m <sup>2</sup> pass 等级 Bfl-s1 ≥8kW/m <sup>2</sup> 通过
Slip resistance 防滑		EN 13893 DIN 51130	DS R10
Flexibility 弯曲性		EN ISO 24344	Pass 通过
Light fastness 色牢度		EN ISO 105-BO2	≥6
Wear resistance 耐磨性		EN 660-2	Group T T级
Castor chair abrasion 椅子脚轮试验		EN 425	Pass 通过
Indentation 残余凹陷		EN ISO 24343	≤ 0.10mm
Sound insulation 隔音		ISO 140-8	ca. 4dB
Chemical resistance 耐污染性		EN ISO 26987	Good 好
Under floor heating 地板采暖		EN 12667	Suitable 适用
Electrical behaviours 导电性		EN 1815	≤ 2kV Antistatic ≤ 2kV 抗静电
VOC emissions VOC排放		Section 01350 / Floorscore	Pass 通过

All information is correct at the time of print and is subject to change without prior notice. Visit us online for more information and updates. This product has never contained phthalate plasticisers. 所有信息在印刷时都经过校对，如有更改，恕不另行通知。在线访问我们获取更多信息和更新。该产品从未使用过邻苯类增塑剂。 [www.altro.com](http://www.altro.com), [www.altro.net.cn](http://www.altro.net.cn)