



















## Altro Classic™ 25 / X25 & Altro Atlas™ 40 / X40

Flooring type 地板类型		EN 13845/ EN 13553	Safety flooring 安全地板
Classification for use 使用等级分类		EN 685	34 & 43
Slip resistance 防滑		TRRL EN 13845 EN 13893 DIN 51130	X25 - ≥45 X40 - ≥36 ESf DS X25 - R11 X40 - R10
Thickness 厚度		EN 428	X25 - 2.5mm X40 - 4mm
Wear layer 耐磨层		EN 429	X25 - 2.5mm X40 - 4mm
Flexibility 弯曲性		EN 435	Pass 通过
Weight 重量		EN 430	X25 - 3.2 kg/m <sup>2</sup> X40 - 5.6 kg/m <sup>2</sup>
Roll dimensions 成卷尺寸		EN 426	X25 2 m x 20 m = 40m <sup>2</sup> X40 2 m x 12.5 m = 25m <sup>2</sup>
Light fastness 色牢度		EN 20105-B02	≥6
Sound insulation 隔音		ISO 140-8	X25 5 dB X40 7 dB
Wear resistance 耐磨性		EN 13845	≤10% particles lost over 50000 cycles ≤10% 颗粒损失 50000转
Indentation 残余凹陷		EN 433	≤ 0.10mm
Fire performance 防火		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 ≥8kW/m <sup>2</sup> pass 等级 Bfl-s1 ≥8kW/m <sup>2</sup> 通过
Chemical resistance 耐污染性		EN 423	Good 好
Castor chair abrasion 椅子脚轮试验		EN 425	Pass 通过
Under floor heating 地板采暖		EN 12667	Suitable 适用
Electrical behaviours 导电性		EN 1815	≤ 2kV Antistatic ≤ 2kV 抗静电
VOC emissions VOC排放		prEN 15052 Section 01350 AgBB/DiBt	Low / Pass / Approved 低 / 通过 / 批准