



altro

EcoFix™ 35 Spray

This spray adhesive may be used with resilient sheet vinyl flooring.
Not recommended for wet areas.

Coverage: 150 - 185 ft² (14 - 17.2 m²)

5 year warranty

Warranted for: 8lbs MVER, 98% RH, 11pH

Product characteristics

EcoFix 35 Spray is a versatile spray adhesive suited for adhering resilient sheet vinyl flooring products in commercial and residential applications.

- Uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive.
- EcoFix 35 Spray's instant shear strength allows for all traffic without any adhesive indentation, displacement or movement associated with heavy weight-bearing loads.
- Non-toxic, 0.020 g/ml low-VOC product.

Coverage guide

Covers 150-185 sq ft

Note: Seams and perimeter require double coverage.

Adhesive coverage is only an approximation based on experience, manufacturers recommendations, and subfloor texture and porosity, Altro does not warrant nor guarantee actual adhesive coverages.

Advantages

- Uses up to 80% less adhesive
- Same day heat welding
- Allows all traffic immediately
- Low-VOC (0.020 g/ml)
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Cleans up easily while still wet
- Non-flammable
- High moisture and pH resistant
- FloorScore certified

Suitable substrates

The following properly prepared, smooth, flat, dust-free substrates are approved:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

Warning: Not to be used in any wet areas (kitchens, bathrooms, pools, etc.)



LEED facts

LEED v4 This product may help contribute to the following credits

EcoFix 35 Spray **1**

Environmental quality
Low emitting materials, adhesives **1**

Discover more of our sustainability story and credentials at altro.com

Technical data		Characteristics
Chemical type	Water-based acrylic blend	Provides immediate shear strength after installation allowing instant access to finished floor.
Appearance	Milky white frost bubbles	
Flash point	Will not burn	
NFPA 704 flammability rating	0 (Non-flammable)	Solvent-free, emits no harmful fumes and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.
Shelf life	3 years, if unopened	
Open time	3 hours	Uses non-ozone depleting HFC propellant.
Dry time	Once adhesive is dry to touch (10-20 minutes)	
Foot traffic allowance	Immediately	Withstands 8 lbs. of vapor emissions, 98% RH and 11 pH.
Heavy machinery allowance	Immediately	
Resistance to moisture	Excellent: 8 lbs/1,000 sq ft or 98% RH/11pH	
Underfloor heating systems	Yes	
Storage	Do not subject to freezing temperatures	