





















## Altro Stronghold™ 30 / K30

|                                  |   |   |   |
|----------------------------------|---|---|---|
| Flooring type<br>地板类型            |       | EN 13845/<br>EN 13553                         | Safety flooring<br>安全地板   |
| Classification for use<br>使用等级分类 |       | EN 685  | 34 & 43   |
| Slip resistance<br>防滑            |       | TRRL<br>EN 13845<br>EN 13893<br>DIN 51130     | ≥ 55 Class 3 / 等级 3<br>ESf<br>DS<br>R12                                   |
| Thickness<br>厚度                  |    | EN 428  | 3 mm  |
| Wear layer<br>耐磨层                |   | EN 429  | 3 mm  |
| Flexibility<br>弯曲性               |    | EN 435  | Pass<br>通过  |
| Weight<br>重量                     |    | EN 430  | 3.9 kg/m <sup>2</sup>   |
| Roll dimensions<br>成卷尺寸          |   | EN 426  | 2 m x 15 m = 30 m <sup>2</sup>  |
| Light fastness<br>色牢度            |    | EN 20105-B02                                  | ≥6  |
| Sound insulation<br>隔音           |    | ISO 140-8                                     | 10 dB   |
| Wear resistance<br>耐磨性           |    | EN 13845                                      | ≤10% particles lost over 50000 cycles<br>≤10% 颗粒损失 50000转                 |
| Indentation<br>残余凹陷              |    | EN 433  | ≤ 0.10mm  |
| Fire performance<br>防火           |    | EN 13501-1<br>EN ISO 9239-1<br>EN ISO 11925-2 | Class Bfl-s1 ≥8kW/m <sup>2</sup> pass<br>等级 Bfl-s1 ≥8kW/m <sup>2</sup> 通过 |
| Chemical resistance<br>耐污染性      |    | EN 423  | Good<br>好   |
| Castor chair abrasion<br>椅子脚轮试验  |    | EN 425  | Pass<br>通过  |
| Under floor heating<br>地板采暖      |    | EN 12667                                      | Suitable<br>适用  |
| Electrical behaviours<br>导电性     |    | EN 1815                                       | ≤ 2kV Antistatic<br>≤ 2kV 抗静电   |
| VOC emissions<br>VOC排放           |    | prEN 15052<br>Section 01350<br>AgBB/DiBt      | Low / Pass / Approved<br>低 / 通过 / 批准                                      |